project 1TM 6000 SERIES GENERAL PURPOSE RTV SILICONE



PROJECT 1[™] 6000 SERIES-GENERAL PURPOSE RTV SILICONE SEALANT is a high quality, single-component, silicone sealant providing a waterproof seal in many construction and industrial applications. This product is suitable for interior and exterior use. It adheres to metal, glass, marble, tile, ceramic, porcelain, painted surfaces, non-oily woods, rubber, and many plastics. It can be used as an adhesive for bonding surfaces together. Project 1[™] RTV Silicone offers long-life reliability, good adhesion, and excellent weatherability. This product is also available in Removable nozzle.

TYPICAL PROPERTIES

As Supplied

Colors	Clear, White, Black and Alumi
Specific Gravity at 77° (25°)	
Extrusion Rate (3.18mm orifice, 90 psi air press	ure)g/min350
Flow, Sag, Slump	NII
Application Temperature Range, °F (°C)	35 to 140(-37 to 60)
Tooling Time, Minutes	
Tack Free Time, Minutes	
Cure Time at 77° (25°) and 50% RH (3.18mm th	nickness),hrs24

As Cured (7 days)

Durometer Hardness, Shore A, points (ASTM 2240)	
Tensile Strength, psi (ASTM D412)	
Elongation, percent (ASTM D412)	
Brittle Point, F (C) (ASTM D746)	
Tear Strength, ppi	
Temperature Range:	
Continuous operating temperature, max	350° F
Intermittent operating temperature, max	450° F

Limitations - Project 1[™] Silicone is not recommended for use in applications involving:

- Temperatures exceeding 450°F
- Structural silicone glazing
- For use on vinyl windows and/or siding
- Prolonged water immersion
- Porous surfaces such as concrete, fiberglass, and some plastics
- Materials that bleed oils or solvents
- Surfaces to be painted...conventional paints will not adhere.

Packaging:

Project 1[™] Silicone is supplied in a 10.1oz (300ml) caulking cartridge, 5 gallon pails, and 55 gallon drums.

Warranty and Shelf Life:

Each application should be pre-tested for suitability of this product for the intended use. When stored in the original, unopened container at temperatures less than 90° F (32° C), Project 1TM Silicone is guaranteed for one year from date of purchase.

www.HitecIndustries.com